





①	<b>2x OUTPUT</b> 30 VDC - 20 mA max. - SELV	x= 7 mm 0.14 mm <sup>2</sup> - 1.5 mm <sup>2</sup>	0.25 N.m max.
②	<b>3x INPUT</b> 12 VDC - 27 mA max. - SELV	x= 7 mm 0.14 mm <sup>2</sup> - 1.5 mm <sup>2</sup>	0.25 N.m max.
③	<b>RS485 MODBUS SELV</b>	x= 7 mm 0.14 mm <sup>2</sup> - 1.5 mm <sup>2</sup>	0.25 N.m max.
④	<b>SUPPLY</b> 110-400 VAC 50-60Hz 120-300 VDC	x= 7 mm 0.2 mm <sup>2</sup> - 2.5 mm <sup>2</sup>	0.6 N.m max.
⑤	<b>V1-V2-V3-VN</b> 50-300 VAC (L/N) 87-520 VAC (L/L')	x= 7 mm 0.2 mm <sup>2</sup> - 2.5 mm <sup>2</sup>	0.6 N.m max.
⑥	<b>ETHERNET (Ref 4825 0501)</b> <b>PROFIBUS (Ref 4825 0502)</b>	-	-
⑦		x= 8 mm 0.2 mm <sup>2</sup> - 4 mm <sup>2</sup>	0.6 N.m max.

SELV: Safety Extra Low Voltage

