

Selection guide

Indicators and transducers

What function?



What characteristics?

Analogue



AC and DC measurements

Characteristics


Type	DIN - ROTEX
Indication, display or output	Pointer deflection: 90°
Mounting	Flush-mounted; modular on DIN rail
Format	48 x 48 - 72 x 72 - 96 x 96 (mm)

AC measurements

Current measurements	Direct 1 to 100 A On 5 A CT Indication: I_n ; 5 I_n	Standard ammeter
Voltage measurement	Direct 6 to 600 V	Indication: U_n Standard or switch voltmeter
Active power measurement		
Timers	Voltage 24 to 400 VAC	

DC measurement

Current measurement	Direct 100 μ A to 50 A	On shunt 100 mv
Voltage measurement	Direct 25 to 500 V	
Timers and pulse counters	Voltage 10 to 220 VDC	
Other measurement	Synchronisation devices Temperature measurement	Other values Maritime applications Railway applications



Transducers	
Measuring transducers	
CS - CM	
Standardised analogue output	
Protruding or modular on DIN rail	
CS: 75 or 150 mm; CM: 6 modules	
Direct 1 to 5 A Self-powered or with auxiliary power supply	Current output 4 ... 20 mA
400 V voltage 5 A CT	With auxiliary power supply Current output 4 ... 20 mA